

Smartflex SMT Comfort

5-layer garden hose with innovative SMT fabric with claw coupling

Applications	irrigation
Structure	soft PVC, grey, opaque, SMT knitting
Temperature	-15°C up to 65°C
Properties	excellent flexibility, good tensile strength, crush-resistant, can be driven over, very high pressure resistance, good ozone- & UV-resistance, hydrolysis & microbe resistant, weather proof, rot proof, phthalate-free



Inner Diameter (mm)	Outer Diameter (mm)	Wall Thickness (mm)	Bending Radius (mm)	Max. Operating Pressure (bar)	Weight (kg/m)	Total Weight per Piece (kg)	Length (m)	Article Number
12,5	17,40	2,45	65	14,00	0,14000	3,50	25	110801013025
12,5	17,40	2,45	65	14,00	0,14000	7,00	50	110801013050
16	21,30	2,65	90	12,00	0,18000	4,50	25	110801016025
16	21,30	2,65	90	12,00	0,18000	9,00	50	110801016050
19	25,40	3,20	105	9,00	0,27000	6,75	25	110801019025
19	25,40	3,20	105	9,00	0,27000	13,50	50	110801019050
25	32,80	3,90	125	7,00	0,43000	10,75	25	110801025025
25	32,80	3,90	125	7,00	0,43000	21,50	50	110801025050